



Einschubprofil Nr. 144, 27 x 8 mm

Universalabschlussprofile sind für verschiedene Bodenbeläge, von nur 2 mm dünnen Designböden bis hin zu 22 mm starken Massivholzdielen, erhältlich und universell einsetzbar.

- Aluminium.
- Für Belagstärken von 5,5-6 mm.
- Versenkte Schraublöcher.
- Als Abschlussprofil sowie als Türanschlagprofil geeignet.

Werkstoff: EN AW 6063 (DIN EN 573)
Werkstoffzustand: T6 (DIN EN 755-2)
Vorbehandlung: E6 (DIN EN 17 611)
Schichtdicke Eloxal: Klasse 15 (DIN EN 17 611)

Zubehör: Befestigungsmaterial.
Geeignet für: Designbelag / LVT, Textile Bodenbeläge
Montageart: Schrauben
Längen: 500 / 250 / 100 cm
Farbauswahl: sahara, silber, Edelstahl matt



Border section no. 144, 29 x 8 mm

Universal edge sections are available for various floor coverings. They can be used with only 2 mm thin design floorings up to 22 mm thick solid wood flooring.

- Aluminium.
- For floor coverings 5,5-6 mm.
- Countersunk holes.
- Suitable as end section as well as door stopping section.

Material: EN AW 6063 (DIN EN 573)
Material condition: T6 (DIN EN 755-2)
Pre-treatment: E6 (DIN EN 17 611)
Thickness of anodised layer: Class 15 (DIN EN 17 611)

Accessories: Fastening material.
Suitable for: design flooring / LVT, textile floor coverings
Installation: screwing
Lengths: 500 / 250 / 100 cm
Colours: sahara, silver, stainless steel matt