



RubberKork 2 mm

+Verbessert Trittschall und Gehkomfort.

+Für stark frequentierte Räume und den Einsatz im Objektbereich.

+Sehr gute Druckstabilität.

- Für die beidseitig vollflächige Verklebung von Fertigparkett, Teppichboden, Linoleum und homogenen PVC-Bodenbelägen.
- Für die schwimmende Verlegung von Laminat und Fertigparkett sowie Vinylböden mit Click-Verbindung.
- Hochwertige Trittschall-Entkopplungsmatte aus Kork- Gummigranulat, PU-Elastomer gebunden.

RubberCork 2 mm

+Improves impact sound and walking comfort.

+For high traffic areas and for application in commercial properties.

+Very good pressure resistance.

- For the full surface gluing on both sides of prefabricated parquet, fitted carpets, linoleum and homogeneous PVC floor coverings.
- For the floating installation of laminate and parquet as well as vinyl flooring with click connection.
- High-quality noise decoupling mats made of cork and rubber granulates, with PU elastomer bounding agent.

Technische Daten

Trittschalldämmung	[IS]	●●●●●	25 dB(A)	Impact Sound
Gehschalldämmung	[RWS]	belagabhängig / flooring dependent		Reflected Walking Sound
Gehschallabstrahlung	[sone]	●●●●●	93 sone	Emitted Walking Sound
Wärmedurchlasswiderstand	[R]	○○○○○	0,041 m² K/W	Thermal Resistance
Eignung auf Fußbodenheizung		●●●●●	ja / yes	Suitable on underfloor heating
Punktuelle Ausgleich	[PC]	●●○○○	0,7 mm	Punktual Conformability
Feuchteschutz	[SD]	○○○○○		Moisture protection
Druckbeanspruchung	[CS]	●●●●○	70 kPa	Compressive Strenght

Technical data

Impact Sound
Reflected Walking Sound
Emitted Walking Sound
Thermal Resistance
Suitable on underfloor heating
Punktual Conformability
Moisture protection
Compressive Strenght

