



LVT Silent PUR GRIP 1,4 mm

- +Für schwimmend verlegte LVT-Click-Bodenbeläge.
- +Rutschhemmende GRIP-Oberfläche minimiert den Drift des Bodenbelags.
- +Für stark frequentierte Räume und den Einsatz im Objektbereich.

- Dauerelastische, alterungsbeständige Polyurethan-Schwermatte aus 90% natürlichen Rohstoffen, PU-Bindemittel und mineralischen Füllstoffen.
- Rutschhemmende GRIP-Oberfläche ohne Klebstoffzusätze.
- Verhindert ein Verrutschen des Belags bei der Verriegelung.
- Hohes Rückstellvermögen.

LVT Silent PUR GRIP 1.4 mm

- +For floating LVT click floor coverings.
- +Non-slip GRIP surface keeps the floor covering from drifting.
- +For high traffic areas and for application in commercial properties.

- Permanently elastic, non-ageing polyurethane underlay from 90% natural materials, PU-bonding agent and with mineral fillers.
- Non-slip GRIP surface without adhesive additives.
- Prevents the flooring from drifting during locking.
- High resilience.

Technische Daten

Trittschallreduzierung	[IS]	●●○○○	15 dB(A)
Gehschallreduzierung	[RWS]	●●○○○	6 %
Wärmedurchlasswiderstand	[R]	○○○○○	0,01 m² K/W
Eignung auf Fußbodenheizung		●●●●●	ja / yes
Punktuellder Ausgleich	[PC]	●●○○○	0,62 mm
Feuchteschutz	[SD]	○○○○○	
Druckbeanspruchung	[CS]	●●●●●	440 kPa
Dynamische Beanspruchung	[DL]	●●○○○	100.000 Zyklen
Dauerhafte Druckbeanspruchung	[CC]	●●●●○	76 kPa
Stoßbeanspruchung	[RLB]	●●●○○	600 mm
Anti-Rutsch-Oberfläche		●●●●●	

Technical data

Impact Sound	
Reflected Walking Sound	
Thermal Resistance	
Suitable on underfloor heating	
Punktual Conformability	
Moisture protection	
Compressive Strenght	
Dynamic Load	
Compressive Creep	
Resistance to Large Ball	
Anti-slip surface	



Frei von Formaldehyd
und flüchtigen organi-
schen Verbindungen.
Free of formaldehyde
and volatile organic
compounds.



Ökologisch
unbedenklich
Ecologically
safe

