

Winkelprofil

Nr. 160, 24,5 x 10 mm

**Winkelprofile sind ideal geeignet als kleiner Treppenwinkel, als Türschwellenprofil oder als Abschluss an Podesten.
Sie schützen die Kanten des Bodenbelags dauerhaft.**

- Aluminium.
- Selbstklebend.

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)
Dekorfolie:	optional (Holzdekore)


Klebstoff	
Schmelzhaftklebstoff (synthetische Kautschukbasis)	
Viskosität:	10.000 +/- 3.000 mPa.s (170°C)
(Brookfield RVT DV-II, Sp 27 ASTM D 3236)	
FDA Status:	gemäß § 175.105 Adhesives
Transportschutz:	abgedeckt mit Silikonpapier

Geeignet für: Designbelag / LVT, Elastische Bodenbeläge, Textile Bodenbeläge, Laminat / Multilayer

Montageart: Kleben

Längen: 270 / 100 / 90 / 300 cm

Farbauswahl: gold, sahara, silber, bronze, Edelstahl matt, Edelstahl gebürstet, schwarz pulverbeschichtet, Buche, Eiche dunkel, Eiche hell, Ahorn, Nussbaum, Eiche hell, Eiche grau



Angle edge

no. 160, 24.5 x 10 mm

**Angle edges are ideally suited as a small staircase angle, as a door threshold profile or as a termination on platforms.
They protect the edges of the flooring permanently.**

- Aluminium.
- Auto-adhesive.

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)
Decorative foil:	optional (wooden decors)

Adhesive	
hotmelt adhesive (synthetic rubber-based)	
Viscosity:	10.000 +/- 3.000 mPa.s (170°C)
(Brookfield RVT DV-II, Sp 27 ASTM D 3236)	
FDA state:	acc. to § 175.105 Adhesives
Protection:	covered with silicone paper

Suitable for: design flooring / LVT, elastic floor coverings, textile floor coverings, laminate / multilayer

Installation: gluing

Lengths: 270 / 100 / 90 / 300 cm

Colours: gold, sahara, silver, bronze, stainless steel matt, stainless steel brushed, black powdercoated, beech, oak dark, oak light, maple, walnut, oak light, Oak grey